




CITEL

Coaxial surge protector DC-3.5 GHz

P8AX09-N/FF



- RF coaxial surge protector
- 3.5 GHz
- Connectors: N
- Low insertion loss
- Removable GDT
- DC-pass
- Bi-directional protection



Electrical Characteristics

Max. DC operating voltage	Uc	72 Vdc
Frequency range	f	DC-3.5 GHz
Impedance		50 ohms
Residual Current <i>Leakage current to Ground</i>	Ipe	None
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	20 kA
Nominal discharge current <i>C2 Category</i>	I _n	5 kA
Protection level <i>@1kV/μs (C3)</i>	Up	< 650 V
Impulse current <i>2 x 10/350μs Test - D1 Category</i>	I _{imp}	1 kA
Max RF Power		25 W
Typical let through energy <i>(50 ohms) input 4kV 1.2/50μs - 2kA 8/20μs</i>		300 μ J
DC Pass		Yes
Insulation resistance	IR	≥ 10 GOhms

Mechanical Characteristics

Technology	Gas discharge tube
Connection to Network	Connector N Female/Female
Mounting	Bulkhead or Bracket
Housing material	Brass/Surface plating: Cu Zn Sn
Operating temperature	Tu -40/+85°C
Relative Humidity	5 - 85%
Protection rating	IP65
Failsafe mode	Short-circuit
Disconnection indicator	Transmission interrupt
Spare module(s)	BBHF-90V
Dimensions	See diagram
Contacts	Bronze/Surface Au-Ag

Standards

Standards compliance	IEC 61643-21 / EN 61643-21 / UL497E
Environmental standards	EU RoHS

Part number

6000150

